



TECHNICAL SPECIFICATION

FOR

**GROUND AND AIRBORNE MODEL CONTROL
EQUIPMENT**

ISSUED BY

**BOTSWANA COMMUNICATIONS REGULATORY
AUTHORITY**

Document Number: TS0021
Revision: Original V1.1
Date: 11 December 2015

Technical Specification for Ground and Airborne Model Control Equipment

Contents

Scope	3
Entry into Force	3
Document History	3
Spectrum Allocation	4
Health, Safety, and Generic Emissions	4
Technical, Spectrum and EMC Requirements	4
Additional requirements	5

Issued by:

Botswana Communications Regulatory Authority
Plot 50671, Independence Avenue
Private Bag 00495
Gaborone

Tel: +267 395 7755, Fax: +267 395 7976

Email: info@bocra.org.bw

Website: www.bocra.org.bw

Scope

This specification applies to all ground and airborne model control equipment to be used in Botswana.

Where terminal equipment supports more than one interface type, each interface must meet the requirements applicable to it. It may therefore be necessary to make reference to additional specifications.

Entry into Force

This specification shall enter into force on 15/01/2016.

Document History

Description	Status	Date
Ground and Airborne Model Control Equipment	Original V1.1	11/12/2015

Spectrum Allocation

The following frequency bands have been allocated for use by ground and airborne model control equipment in Botswana:

Ground: 26.995 MHz, 27.045 MHz, 27.095 MHz, 27.145 MHz and 27.195 MHz.

Airborne: 35.000 – 35.250 MHz

Health, Safety, and Generic Emissions

The following universal specifications shall be applied.

TS0001: Health, Safety and Generic Emissions of Radio and Telecommunications Terminal Equipment.

Technical, Spectrum and EMC Requirements

The following specifications shall be applied.

ETSI EN 300 220-1 V2.4.1

Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1000 MHz frequency range with power levels ranging up to 500 mW; Part 1: Technical characteristics and test methods

ETSI EN 300 220-2 V2.4.1

Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 2: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive

ETSI EN 300 220-3 V1.1.1

Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW; Part 3: Harmonized EN covering essential requirements under article 3.2 of the R&TTE Directive

ETSI EN 301 489-1 V1.9.2

Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements

ETSI EN 301 489-3 V1.6.1

Electromagnetic compatibility and Radio spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 3: Specific conditions for Short Range Devices (SRD) operating on frequencies between 9 kHz and 246 GHz

Important Note: The revision numbers of the documents given in the approval standard are the minimum standards that apply. Should updated versions of these documents be published, the latest version will always apply. This also applies to documents where no revision number is currently quoted.

Additional Requirements

Additional requirements may exist for the use of ground and airborne model control equipment. A licence must be obtained before equipment of this type can be used in Botswana. This licence will detail conditions of use and any additional requirements which must be met.

Obtaining Technical Standards

ETSI technical standards may be obtained free of charge for individual use from the ETSI web site. www.etsi.org

CENELEC, IEC and CISPR standards may be obtained at cost from, or through www.cenelec.org and from www.iec.ch respectively.